

DATA SHEET



NAME:

ECOfelt

DESCRIPTION:


Sound-absorbing and anti-reverberation layers

APPLICATIONS:

- Wall with glue or double sided tape
- Ceiling with glue or double sided tape
- Furniture with glue or double sided tape
- Upholstery, panels
- Curtains



DATA SHEET



DIMENSIONS:

- Length (min.) 2500 x H 150 cm x THK 1,5 | 3 | 4,5 | 6 | 8 mm
- Length (min.) 984.25 x H 59 in x THK 0.06 | 0.12 | 0.18 | 0.24 | 0.32 in

NOTE: Custom cuts on request ECOfelt **4,5** mm (**0.18** in), NO minimum length **2500** cm (**984.25** in)

WEIGHT:

eight

• 1,5 mm (0.06 in)	420 gr/mtl - 0.92 lb/ft

- 3 mm (0.12 in) 820 gr/mtl 1.8 lb/ft
- 4,5 mm (0.18 in) 1200 gr/mtl 2.6 lb/ft
- •6 mm (0.24 in) 1630 gr/mtl 3.6 lb/ft
- 8 mm (0.32 in) 2000 gr/mtl 4.4 lb/ft



DATA SHEET

COMPOSITION:

• ECOfelt - 90% wool, 10% polyester

COLOR DIFFERENCES:

Slight differences between dyeing lots are considered normal

INSTALLATION ADVICE:

Slalom recommends installers with at least 4 years of experience in the installation of upholstery products

- 1,5 mm (0.06 in): ONLY for upholstery
- 3 mm (0.12 in): for surfaces, ONLY for very experienced installers
- from 4,5 mm (0.18 in): for surfaces

RECYCLABILITY:

Textile ecology of natural wool felts, recyclable in respect of the environment

MAINTENANCE:

Regularly and carefully use the vacuum cleaner with a smooth spout, or use soft bristle brushes or professional pads for padding and upholstery





DATA SHEET

CERTIFICATIONS:

- FIRE REACTION CLASS UE: B-s2, d0 - OPTIONAL
- FIRE REACTION CLASS USA: Class A - ASTM E 84-18 – OPTIONAL
- GREEN LABELS:


GREENGUARD GREENGUARDGOLD

• SOUND ABSORPTION REPORT:

UNI EN ISO 354: 2003 UNI EN ISO 11654: 1998

Felt (THK 3 mm | 0.12 in):


Sample description: Fabric for surface, wall ceiling furniture application, Model " Feltro 3 mm" Mounting Type: A



Evaluation based on laboratory measurement results by means of a technical method.

Felt (THK 4,5 mm | 0.18 in):

Sample description: Fabric for surface, wall ceiling furniture application, Model " Feltro 4.5 mm" Mounting Type: A




Evaluation based on laboratory measurement results by means of a technical method.



11.52 m² Sample area: Reverberation room volume: 161.3 m³ f [Hz] αs [-] 1,0 Acoustic absorption coefficient values Frequency 0.9 0,8 100 0.01 absorption coefficient α_s [-] 125 0.00 0,7 160 0.03 200 0.03 0,6 250 0.04 0,5 315 0.05 400 0.07 0.4 500 0.10 Acoustic 630 0.14 0,3 800 0.18 0,2 1000 0.24 1250 0.33 0,1 1600 0.39 2000 0.46 0,0 2500 0.50 3150 0.57 4000 0.59 Frequency [Hz] 5000 0.63

Felt (THK 8 mm | 0.32 in):

Sample description: Fabric for surface, wall ceiling furniture application, Model " Feltro 8 mm" Mounting Type: A



Evaluation based on laboratory measurement results by means of a technical method

Sample description: Fabric for surface, wall ceiling furniture application, Model " Feltro 6 mm" Mounting Type: A

Evaluation based on laboratory measurement results by means of a technical method.

Felt (THK 6 mm | 0.24 in):



COMPOSITION

90% lana naturale, 10% poliestere 90% natural wool, 10% polyester

ECOfelt

					2.44
Ghost white 955E	Chalk 327	Grey 953E	Concrete 903	Beige 952	Caramel 332E
Mushroom 325	Chocolate 352	Taupe 511	Brown 605	Rust 604	Corten 516
Yellow 34	Egg 980	Mustard 54	Cob orange 997	Orange 971	Coral 336
Red 5	Pompei 47	Bordeaux 192	Marsala 973	Quartz rose 940	Salmon 317
with the					
Bubble pink 53	Pink 988	Marylin 323	Mauve 601	Agate 919	Violet 921
Purple 508	Barolo 602	Grape 603	Fresh air 976	Salvia green 334E	Acid green 611E
Cashmere green 8	9 Grassland 937	Tea Green 345	Leaf Green 910	Lagoon 608	Peacock blue 962
Black forest 77	Dark musk 22E	Mineral Blue 311	Biggest Splash 41	Capri 341	Avio 333E
Light blue 914	Blue yonder 200	Azuleja 318	Moonstone 512	Skyblue 942	Nynph 972
Honolulu blue 607	Blue 193	Blue Klein 322	Deep sea blue 963	Ink 329	Dark grey 923