


# Minerval® A 15

White decorative glass fiber veil

High density  
stone wool panel,  
15 mm thick



A Edges

Natural glass veil  
on reverse side

## KEY FEATURES

- Acoustic absorption:  $\alpha_w = 0.95$
- Reaction to fire: A1
- 100% flat irrespective of the Relative Humidity
- Reverse side veil






White

## Minerval® A 15

- > Rigid stone wool self-supporting panel.
- > Decorative white glass fiber veil.
- > Reinforced by a natural glass fiber veil on the reverse side.
- > Designed to be installed on T15 - T24 grids.



### Acoustic absorption



•  $\alpha_w = 0.95$  : class A / NRC = 0.90



### Light reflection

- The light reflection coefficient of the veil is superior to 86%.



### Fire reaction

- According to EN 13501-1: Euroclass A1.



### Humidity performance

- 100% flat irrespective of the Relative Humidity.



### Environment and health

#### Environment

- Mineral wool is recyclable, and the vast majority of production waste is recycled. The recycled content of the mineral wool of our Minerval® A 15 panels is 45%.
- For projects based on LEED®, BREEAM® and HQE™ Green Building certifications, EPD (Environmental Product Declarations) are available. Contact us.
- Eurocoustic is certified to ISO 14001: 2015 «Environmental Management Systems».

#### Healthcare

- Eurocoustic stone wool is certified by EUCEB (European CErtification Board for mineral wool product).
- Stone wool panels are manufactured with fibers exempt from the carcinogenic classification (European Regulation 1272/2008 as amended by European Regulation 790/2009). According to the International Agency for Research on Cancer, mineral wool is not classifiable as to its carcinogenicity to humans (Group 3).



### CE marking

- DoP no.: G001.



### Indoor Air Quality

- Minerval® A 15 products are classed A+.



### Installation

- Installation must conform to the requirements of the DTU 58.1 code of practice, the NF P 68203-1 and 2 standards and other applicable standards and codes of practice according to the type of room.
- You are advised to ensure that air can circulate between the rooms and the plenum to balance the temperature and pressures on each side of the ceiling.
- Minerval® A 15 ceilings are fitted on T15 - T24 grids.
- Tiles can be cut with a craft knife without generating any noise or dust.
- The direction in which the panels should be installed is indicated on the back of the panels.
- Contact us if any mineral wool is to be laid in the plenum.



### Cleaning

- The surface of Minerval® A 15 ceilings does not retain dust, which makes them easier to clean.
- Minerval® A 15 ceilings can be cleaned using light brush / vacuum cleaner.
- This type of cleaning will help extend the service life of Minerval® A 15 ceilings.

### AT A GLANCE

Color	White
Edges	A
Grids	T15 - T24

### Module size (mm) and packaging

Width	600	600
Length	600	1200
Thickness	15	15
Panels/pack	32	16
m <sup>2</sup> /pack	11,52	11,52
Packs/pallet	18	18

Minerval® A 15 ceiling packs are shrink-wrapped for protection. Pallets are wrapped in plastic film and must be stored under cover.