

DESCRIPTION:

Multi Cover Air Plus is a self-adhering fleece used to temporarily protect floors and stairs. The fleece consists of two layers. The anti-slip bottom layer is non-woven and has a special water-resistant adhesive layer. This ensures it always remains fixed in place on the floor. The top layer allows any residual moisture to evaporate from the underlying floor. The top of this membrane is waterproof. Multi Cover Air Plus can be placed quickly and easily to protect floors and stairs.



APPLICATIONS::

- COVERING FOR HARD FLOORS
- COVERING FOR LACQUERED STAIRS
- COVERING FOR PREFABRICATED CONCRETE
- COVERING FOR PREFABRICATED STAIRS
- COVERING FOR PREFABRICATED BALCONIES
- COVERING FOR PARQUET FLOORS
- COVERING FOR LACQUERED STAIRS

CHARACTERISTICS:

- QUICK AND EASY TO USE
- SAFE TO WALK ON THANKS TO THE ANTI-SLIP LAYER
- SHOCK-ABSORBING AND WATERPROOF TOP LAYER
- PERMEABLE BOTTOM LAYER
- REUSABLE
- SUITABLE FOR COVERING STAIRS THANKS TO THE CONVENIENT FORMAT

TECHNICAL DATA:

| | |
|---------------------------|--|
| Application duration | 3 months (max 40° C) |
| Storage | 12 months (5° – 30° C) (dry, no direct sunlight) |
| Thickness | 2.5mm +/- 10% |
| Weight | 160 gr/m2 |
| Tensile Strength (MD) | Min. 100N/5cm |
| Tensile Strength (CD) | Min. 100N/5cm |
| Elongation @ Fmax [MD] | Max. 125% |
| Elongation @ Fmax [CD] | Max. 150% |
| Skid ability | 150 N / A4 Sample |
| Water vapour permeability | 70 gr/m2/24hr |
| Winding | Reversed wound (Glue on the outside) |
| Core | Carboard Tube |

COMPOSITION:

| | |
|------------|--|
| Material | Non-woven produced with 100% PES fiber |
| Adhesive | Acrylic waterbased |
| Colour | White |
| Laminated: | Breathable PE-film |